



- Product type: Connectors with spring-cape clamp,
- Wiring method: spring clip connection,
- Spacing: 3.50mm(.138"),
- Voltage: 300V,
- Current: 8A,
- Number of digits: 2-24P

BASICPARAMETERS

Pitch:	3.50mm(.138")
Rated voltage-UL:	300V
Rated current-UL:	8A
Rated voltage-IEC:	250V
Rated current-IEC:	10A
Wire range-UL:	28-14AWG
Wire range-IEC:	1.5mm²
Pole number:	02~24P
Insulation Material:	PA66 UL94 V-0
Material & Plating of Current carrier:	Copper alloy, Tin plated
Insulation Resistance:	500MΩ or more at DC500V
Withstanding Voltage(1Min):	AC2200V/Min
Rated surge voltage:	2500V
Wire clamp unit Screw, torque Max.:	-
Mounting Screw, torque:	-
7.0 Material of Clamp spring:	Stainless Steel
Wire stripping length:	7.0mm
Operating temperature:	-40℃ ~ +115℃
Soldering recommend:	-
Approval:	 

DIMENSION DRAWING

订购产品

Product Name	Pitch	Pole number	Part No.	3D Download	2D Download
MCS Terminal	3.50mm(.138")	02~24P	43540X		

Data download

PRODUCT CATALOG	Terminal Selection Manual
-----------------	---